Stepan 5

SAFETY DATA SHEET

1. Identification

Product identifier STEOL CS-460

Other means of identification

Product code 1808 Recommended use Surfactant

Recommended restrictions For industrial use only. Manufacturer/Importer/Supplier/Distributor information

Manufacturer

Stepan Company Company name 22 West Frontage Road **Address** Northfield, IL 60093

USA

General 1-847-446-7500 **Telephone**

E-mail Not available.

1-800-228-5635 **Emergency phone number** Medical

Chemtrec 1-800-424-9300 Chemtrec Int'l +1 703-527-3887

2. Hazard(s) identification

Flammable liquids Category 3 **Physical hazards** Skin corrosion/irritation Category 2 **Health hazards**

Serious eye damage/eye irritation Category 1

Environmental hazards Hazardous to the aquatic environment, acute Category 2

Hazardous to the aquatic environment, Category 3

long-term hazard

OSHA defined hazards Not classified.

Label elements



Danger Signal word

Hazard statement Flammable liquid and vapor. Causes skin irritation. Causes serious eye damage. Toxic to aquatic

life. Harmful to aquatic life with long lasting effects.

Precautionary statement

Prevention Keep container tightly closed. Keep away from heat/sparks/open flames/hot surfaces. - No

smoking. Ground/bond container and receiving equipment. Use explosion-proof

electrical/ventilating/lighting equipment. Use only non-sparking tools. Take precautionary measures against static discharge. Wash thoroughly after handling. Avoid release to the

environment. Wear protective gloves/eye protection/face protection.

If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower. Response

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a poison center/doctor. Specific treatment (see this label). If skin irritation occurs: Get medical advice/attention. Take off contaminated clothing

and wash before reuse. In case of fire: Use appropriate media to extinguish.

Storage Store in a well-ventilated place. Keep cool.

Dispose of contents/container in accordance with local/regional/national/international regulations. **Disposal**

Hazard(s) not otherwise

Static accumulating flammable liquid can become electrostatically charged even in bonded and

classified (HNOC) grounded equipment. Sparks may ignite liquid and vapor. May cause flash fire or explosion.

Supplemental information None.

Material name: STEOL CS-460 SDS US

Material ID: 1211 Product code: 1808 Version #: 05 Revision date: 07-30-2018 Print date: 07-30-2018

3. Composition/information on ingredients

Mixtures

Chemical name	Common name and synonyms	CAS number	%
_Sodium laureth (n=>3) sulfate		9004-82-4	58 - < 61
Water		7732-18-5	23 - < 27
Ethanol		64-17-5	13 - < 16
Alcohols (c12-15 Ln. Saturated) Ethoxylate		68131-39-5	0 - 3
Other components below reportable	e levels		1 - < 3

4. First-aid measures

Eye contact

Ingestion

Inhalation Move to fresh air. Call a physician if symptoms develop or persist.

Skin contact Take off immediately all contaminated clothing. Rinse skin with water/shower. If skin irritation

occurs: Get medical advice/attention. Take off contaminated clothing and wash before reuse.

Immediately flush eyes with plenty of water for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Get medical attention if irritation develops and persists.

Rinse mouth. Get medical attention if symptoms occur. Do not induce vomiting without advice from

Do not use water jet as an extinguisher, as this will spread the fire.

poison control center.

cause redness and pain.

Most important symptoms/effects, acute and

delayed

Indication of immediate medical attention and special treatment needed

Provide general supportive measures and treat symptomatically. Thermal burns: Flush with water immediately. While flushing, remove clothes which do not adhere to affected area. Call an ambulance. Continue flushing during transport to hospital. Keep victim under observation. Symptoms may be delayed.

Symptoms may include stinging, tearing, redness, swelling, and blurred vision. Skin irritation. May

General information

Take off all contaminated clothing immediately. Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves. Wash contaminated clothing before reuse.

5. Fire-fighting measures

Suitable extinguishing media

Alcohol resistant foam. Water fog. Carbon dioxide (CO2). Dry chemical powder, carbon dioxide, sand or earth may be used for small fires only.

Unsuitable extinguishing media

1eala Inocifio hozordo origina fron

Specific hazards arising from the chemical

Vapors may form explosive mixtures with air. Vapors may travel considerable distance to a source of ignition and flash back. This product is a poor conductor of electricity and can become electrostatically charged. If sufficient charge is accumulated, ignition of flammable mixtures can occur. To reduce potential for static discharge, use proper bonding and grounding procedures. This liquid may accumulate static electricity when filling properly grounded containers. Static electricity accumulation may be significantly increased by the presence of small quantities of water or other contaminants. Material will float and may ignite on surface of water. During fire, gases

hazardous to health may be formed.

Special protective equipment and precautions for firefighters

Self-contained breathing apparatus and full protective clothing must be worn in case of fire.

Fire fighting

equipment/instructions
Specific methods

In case of fire and/or explosion do not breathe fumes. Move containers from fire area if you can do so without risk.

Use standard firefighting procedures and consider the hazards of other involved materials.

General fire hazards Flammable liquid and vapor.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Keep out of low areas. Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Wear appropriate protective equipment and clothing during clean-up. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ventilate closed spaces before entering them. Use appropriate containment to avoid environmental contamination. Local authorities should be advised if significant spillages cannot be contained.

Material name: STEOL CS-460 SDS US

Methods and materials for containment and cleaning up

Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Take precautionary measures against static discharge. Use only non-sparking tools. Keep combustibles (wood, paper, oil, etc.) away from spilled material.

Large Spills: Stop the flow of material, if this is without risk. Dike the spilled material, where this is possible. Cover with plastic sheet to prevent spreading. Use a non-combustible material like vermiculite, sand or earth to soak up the product and place into a container for later disposal. Prevent entry into waterways, sewer, basements or confined areas. Following product recovery, flush area with water.

Small Spills: Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination.

Never return spills to original containers for re-use.

Environmental precautions

Avoid release to the environment. Contact local authorities in case of spillage to drain/aquatic environment. Prevent further leakage or spillage if safe to do so. Do not contaminate water. Avoid discharge into drains, water courses or onto the ground. Use appropriate containment to avoid environmental contamination.

7. Handling and storage

Precautions for safe handling

Vapors may form explosive mixtures with air. Do not handle, store or open near an open flame, sources of heat or sources of ignition. Protect material from direct sunlight. Do not smoke. Minimize fire risks from flammable and combustible materials (including combustible dust and static accumulating liquids) or dangerous reactions with incompatible materials. Handling operations that can promote accumulation of static charges include but are not limited to: mixing, filtering, pumping at high flow rates, splash filling, creating mists or sprays, tank and container filling, tank cleaning, sampling, gauging, switch loading, vacuum truck operations. Take precautionary measures against static discharges. All equipment used when handling the product must be grounded. Use non-sparking tools and explosion-proof equipment. Avoid contact with skin. Avoid contact with eyes. Avoid prolonged exposure. Avoid contact with clothing. Provide adequate ventilation. Wear appropriate personal protective equipment. Observe good industrial hygiene practices. Avoid release to the environment. Do not empty into drains.

Conditions for safe storage, including any incompatibilities

Keep away from heat, sparks and open flame. Prevent electrostatic charge build-up by using common bonding and grounding techniques. Avoid spark promoters. Eliminate sources of ignition. Ground/bond container and equipment. These alone may be insufficient to remove static electricity. Store in original tightly closed container. Store in a cool, dry place out of direct sunlight. Store in a well-ventilated place. Refrigeration recommended. Keep in an area equipped with sprinklers.

8. Exposure controls/personal protection

Occupational exposure limits

US. OSH	IA Table Z-1	Limits for A	Air Contamina	nts (29 CFR	(1910.1000

Components	Туре	Value	
Ethanol (CAS 64-17-5)	PEL	1900 mg/m3	
		1000 ppm	
US. ACGIH Threshold Limit Valu	ies		
Components	Туре	Value	
Ethanol (CAS 64-17-5)	STEL	1000 ppm	
US. NIOSH: Pocket Guide to Ch	emical Hazards		
Components	Type	Value	
Ethanol (CAS 64-17-5)	TWA	1900 mg/m3	
		1000 ppm	

Biological limit values

No biological exposure limits noted for the ingredient(s).

Appropriate engineering controls

Explosion-proof general and local exhaust ventilation. Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level. Eye wash facilities and emergency shower must be available when handling this product.

Individual protection measures, such as personal protective equipment

Eye/face protection Wear safety glasses with side shields (or goggles).

Material name: STEOL CS-460 SDS US

Skin protection

Wear appropriate chemical resistant gloves. Hand protection Other Wear appropriate chemical resistant clothing

Respiratory protection In case of insufficient ventilation, wear suitable respiratory equipment.

Wear appropriate thermal protective clothing, when necessary. Thermal hazards

General hygiene considerations

When using do not smoke. Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work

clothing and protective equipment to remove contaminants.

9. Physical and chemical properties

Appearance Clear. Liquid. **Physical state Form** Liquid. Color Not available.

Not available. Odor **Odor threshold** Not available.

рΗ 7.5 - 9 (10% in water)

25 °F (-3.89 °C) Melting point/freezing point Initial boiling point and boiling 190 °F (87.78 °C)

range

Flash point 78.0 °F (25.6 °C) Pensky-Martens Closed Cup

Not available.

Not available. **Evaporation rate** Flammability (solid, gas) Not available. Upper/lower flammability or explosive limits

Flammability limit - lower

(%)

Flammability limit - upper

19 %

(%)

Explosive limit - lower (%) Not available. Explosive limit - upper (%) Not available. Not available. Vapor pressure Not available. Vapor density Not available. Relative density

Solubility(ies)

Not available. Solubility (water) **Auto-ignition temperature** Not available. Not available. **Decomposition temperature** 55 cP @ 25C **Viscosity**

Other information

Pour point 30 °F (-1.11 °C) Specific gravity 1.03 @ 25C

10. Stability and reactivity

Reactivity The product is stable and non-reactive under normal conditions of use, storage and transport.

Material is stable under normal conditions. **Chemical stability**

Possibility of hazardous

Conditions to avoid

reactions

No dangerous reaction known under conditions of normal use.

Avoid heat, sparks, open flames and other ignition sources. Avoid temperatures exceeding the

flash point. Contact with incompatible materials.

Strong oxidizing agents. Incompatible materials

Hazardous decomposition

products

Upon decomposition, this product may yield sulfur dioxide and oxides of sulfur.

11. Toxicological information

Information on likely routes of exposure

Inhalation Prolonged inhalation may be harmful.

Skin contact Causes skin irritation.

Eye contact Causes serious eye damage.

Ingestion Expected to be a low ingestion hazard.

Not available.

Symptoms related to the physical, chemical and toxicological characteristics

Information on toxicological effects

Acute toxicity

Product Species Test Results

STEOL CS-460

Acute Dermal

Liquid

LD50 Rabbit 2000 - 5000 mg/kg

Oral

Liquid

LD50 Rat > 2000 mg/kg

Skin corrosion/irritation Causes skin irritation.

Serious eye damage/eye

Causes serious eye damage.

irritation

Respiratory or skin sensitization

Respiratory sensitization Not available.

Skin sensitization This product is not expected to cause skin sensitization.

Germ cell mutagenicityNo data available to indicate product or any components present at greater than 0.1% are

mutagenic or genotoxic.

Carcinogenicity This product is not considered to be a carcinogen by IARC, ACGIH, NTP, or OSHA.

IARC Monographs. Overall Evaluation of Carcinogenicity

Not listed.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1052)

Not regulated.

US. National Toxicology Program (NTP) Report on Carcinogens

Not listed.

Reproductive toxicity Contains no ingredient listed as toxic to reproduction

Specific target organ toxicity -

single exposure

Not applicable.

Specific target organ toxicity -

repeated exposure

Not applicable.

Aspiration hazard Not applicable.

12. Ecological information

Ecotoxicity Toxic to aquatic life. Harmful to aquatic life with long lasting effects.

Product Test Results Species STEOL CS-460 Aquatic Acute Algae EC50 Algae > 56 ppm, 72 hours Crustacea EC50 Daphnia > 13 ppm, 48 hours Fish LC50 Fish 2.3 mg/l, 96 hours

Persistence and degradability Readily biodegradable.

Material name: STEOL CS-460 SDS US

Bioaccumulative potential No data available. Partition coefficient n-octanol / water (log Kow)

Ethanol -0.31

Mobility in soil No data available.

Other adverse effects No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation

potential, endocrine disruption, global warming potential) are expected from this component.

13. Disposal considerations

Disposal instructions Dispose of contents/container in accordance with local/regional/national/international regulations.

The waste code should be assigned in discussion between the user, the producer and the waste Hazardous waste code

disposal company.

Waste from residues / unused

products

Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see:

Disposal instructions).

Ethanol Solution

Ethanol Solution

Not available.

Ш

Contaminated packaging Empty containers should be taken to an approved waste handling site for recycling or disposal.

Since emptied containers may retain product residue, follow label warnings even after container is

emptied.

14. Transport information

DOT

UN number UN1170

UN proper shipping name

Transport hazard class(es)

3 Class Subsidiary risk Ш Packing group

Special precautions for user Not available.

IATA

UN number UN1170

UN proper shipping name **Ethanol Solution**

Transport hazard class(es)

3 Class

Subsidiary risk Ш Packing group **Environmental hazards** No.

Special precautions for user Not available.

IMDG

UN number UN1170

UN proper shipping name

Transport hazard class(es)

Class 3 Subsidiary risk

Packing group

Environmental hazards

Marine pollutant No.

EmS Not available.

Special precautions for user Not available.

Transport in bulk according to

Annex II of MARPOL 73/78 and

the IBC Code

DOT



Material name: STEOL CS-460 Material ID: 1211 Product code: 1808 Version #: 05 Revision date: 07-30-2018 Print date: 07-30-2018



15. Regulatory information

Polymer Polymer exempt in the following countries: Europe

This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication US federal regulations

Standard, 29 CFR 1910.1200.

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

Not regulated.

CERCLA Hazardous Substance List (40 CFR 302.4)

Not listed.

SARA 304 Emergency release notification

Not regulated.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1052)

Yes

Not regulated.

Superfund Amendments and Reauthorization Act of 1986 (SARA)

SARA 302 Extremely hazardous substance

Not listed.

SARA 311/312 Hazardous

chemical

Classified hazard

Flammable (gases, aerosols, liquids, or solids) Skin corrosion or irritation

categories

Serious eye damage or eye irritation

Hazard not otherwise classified (HNOC)

SARA 313 (TRI reporting)

Not regulated.

Other federal regulations

Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

Not regulated.

Safe Drinking Water Act

Not regulated.

(SDWA)

FEMA Priority Substances Respiratory Health and Safety in the Flavor Manufacturing Workplace

Ethanol (CAS 64-17-5) Low priority

US state regulations

California Proposition 65



WARNING: This product can expose you to chemicals including Ethylene oxide, which are known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go

to www.P65Warnings.ca.gov.

California Proposition 65 - CRT: Listed date/Carcinogenic substance

1,4-dioxane (CAS 123-91-1) Listed: January 1, 1988 Ethylene oxide (CAS 75-21-8) Listed: July 1, 1987

California Proposition 65 - CRT: Listed date/Developmental toxin

Ethylene oxide (CAS 75-21-8) Listed: August 7, 2009 California Proposition 65 - CRT: Listed date/Female reproductive toxin

Ethylene oxide (CAS 75-21-8) Listed: February 27, 1987

California Proposition 65 - CRT: Listed date/Male reproductive toxin

Ethylene oxide (CAS 75-21-8) Listed: August 7, 2009

Material name: STEOL CS-460 SDS US

International Inventories

Country(s) or region	Inventory name	On inventory (yes/no)*
Australia	Australian Inventory of Chemical Substances (AICS)	Yes
Canada	Domestic Substances List (DSL)	Yes
Canada	Non-Domestic Substances List (NDSL)	No
China	Inventory of Existing Chemical Substances in China (IECSC)	Yes
Japan	Inventory of Existing and New Chemical Substances (ENCS)	Yes
Korea	Existing Chemicals List (ECL)	Yes
New Zealand	New Zealand Inventory (NZIoC)	Yes
Philippines	Philippine Inventory of Chemicals and Chemical Substances (PICCS)	Yes

(PICCS)

Taiwan Taiwan Inventory (TCSI) Yes United States & Puerto Rico Toxic Substances Control Act (TSCA) Inventory Yes

16. Other information, including date of preparation or last revision

06-27-2014 Issue date 07-30-2018 **Revision date**

Version # 05

Terms and Conditions. This SDS is designed only as guidance for the products to which it applies. Disclaimer

To the greatest extent permitted by applicable law, nothing contained herein creates any legal obligation including contractual obligations, expressed or implied warranties, including any warranties of merchantibility or fitness for particular purpose; or confers any intellectual property rights, including rights to use trademarks or a license to use patents, issued or pending. The information contained herein is based on the manufacturer's own study and the work of others, and is subject to change at any time without further notice. There is no warranty, expressed or implied, as to the accuracy, completeness or adequacy of the information contained herein, and neither the provider nor the manufacturer (nor the agents, directors, officers, contractors or employees of either) are liable to any party for any damages of any nature, including direct, special or consequential damages arising out of or in connection with the accuracy, completeness, adequacy or furnishing of any information in this SDS, or in any other way related (directly or indirectly) to this

SDS. The receipt and use of this information constitutes consent to these terms and conditions.

Revision information Identification: Recommended restrictions

Hazard(s) identification: Disposal Hazard(s) identification: Prevention Hazard(s) identification: Response

Hazard(s) identification: Supplemental information Composition / Information on Ingredients: Ingredients Physical & Chemical Properties: Multiple Properties Regulatory information: California Proposition 65

HazReg Data: International Inventories

GHS: Classification

Material name: STEOL CS-460

^{*}A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s) A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).