



Name	RINSE AID	
No.	305	
Description	This formulation is for a low-foaming rinse aid with excellent wetting and drainage that leaves surfaces spot free and sparkling.	
Formulation	INGREDIENTS:	<u>% by Weight</u>
	MAKON® NF-5 STEPANATE® SXS Deionized Water	50.0 15.0 35.0
	Total	100.0
Procedure	Charge tank with Water. Add STEPANATE® SXS and mix. Add MAKON® NF-5 last while under agitation.	
Physical Properties	Appearance at 25ºC Solids, % Cloud point, ºF	Clear liquid 56 76
Instructions for Use	Use at a concentration of 50–200 ppm.	
	Low foaming, excellent wetting, rapid drainage with no break in the water film. Good dispersability at use temperatures. Leaves surfaces sparkling and spot free.	
Registered Trademarks of Stepan Company	MAKON® STEPANATE®	
For Additional	For applications or product handling assistance, call our Technical Service Department at 1-800-745-7837 (U.S.) or 011-334-76-505-100 (Europe). For ordering assistance, call our Account Service Department at 1-800-457-7673.	
Assistance	Nothing contained herein grants or extends a license, express or implied, in connection with patents, issued or pending, of the manufacturer or others. The information contained herein is based on the manufacturer's own study and the works of others. The manufacturer makes no warranties, expressed or implied, as to the accuracy, completeness, or adequacy of the information contained herein. The manufacturer shall not be liable (regardless of fault) to the vendee's employees, or anyone for any direct, special or consequential damages arising out of or in connection with the accuracy, completeness, adequacy or furnishing of such information.	
	Stepan 🍤	
	Stepan Company Northfield, Illinois 60093 Telephone (847) 446-7500	
Revision Date: 01/08/2010 Publication Date: 04/20/2007 © 2010, Stepan Company. All rights reserved.		